

# Installation Instructions

## Prior Recommendations

Before Proceeding with the Installation Check That:

- There is no humidity.
- There are no irregularities in the subfloor (unevenness, holes, etc.).
- There is no direct sunlight. If this is the case, you should use curtains or solar panels.
- Avoid sudden changes in temperature.
- There should not be radiators in the lower part of the room. If so, make sure that the floor temperature does not exceed 100°F.
- There is no floor heating system.
- There is no carpet or elastic surfaces in the subfloor, as it may produce faulty interlocking between the tiles.
- If there is a wooden subfloor, it may darken due to humidity.

## Installation of the Tiles

### Installation Instructions

- Start fitting the tiles in a spiral shape around the initial one (Fig. 1).
- To fit the tiles, press the interlocking down until the joins between the tiles are flat.
- Never force or apply tension while fitting the floor tiles.
- If you wish, you can cut the tiles to make a better fitting in the room.
- Have the pattern facing the same direction.
- Heavy furniture or sports equipment must be placed on the flooring with maximum caution.
- As the final step, do not drag heavy furniture or sports equipment without lifting them by hand, if possible.

### Cutting the Tiles

- Measure the line to be cut (Fig. 2).
- Make a light cut along the previous trim line using the cutter (Fig. 3).
- Make a final cut through the tile (Fig. 4). Be careful not to cut the subfloor.

## Maintenance Advice

### Static Electricity

- In certain environmental conditions, there could be small discharges of static electricity due to the isolating nature of the floor. By using anti-static detergents, this effect will be eliminated.

### Footwear

- The flooring has been designed for use with sports shoes. Wearing regular shoes or high heels may damage the flooring.

### Cleaning

- Use a broom or vacuum to clean the floor properly. Use a mop and standard cleaning product. In case of extreme dirt, scrub the floor with your standard cleaning product and dose as recommended by the manufacturer.
- Do not use polishing wheels, sand, metallic brushes, or steam cleaners on the floor.
- Avoid spilling acids (bathroom products, vinegar, alcohol, bleach, or cleaning products containing fats, solvents, or abrasives).

Figure 1




Figure 2




Figure 3




Figure 4

